

RAVENOL TFE Truck Fuel Efficiency 5W-20

Yopishqoqlik: 5W-20

Sintetik



1 L

Mahsulot kodi:
1121130-001



5 L

Mahsulot kodi:
1121130-005



10 L

Mahsulot kodi:
1121130-010



20 L

Mahsulot kodi:
1121130-020
Mahsulot kodi:
1121130-020-01-999
Shtrix-kod:
4014835887626



20 L, ecobox

Mahsulot kodi:
1121130-B20



60 L

Mahsulot kodi:
1121130-060
Mahsulot kodi:
1121130-060-01-999
Shtrix-kod:
4014835887640



208 L

Mahsulot kodi:
1121130-208
Mahsulot kodi:
1121130-208-01-999
Shtrix-kod:
4014835887664

Xususiyatlari

Ism	Ma'nosi	Audit
Ishlab chiqaruvchi tomonidan ma'qullangan	MAN M 3977, Scania LDF-5	
Zichlik 20°C da	850.6 g/cm ³	EN ISO 12185
Rang	Jigarrang	ingl
Viskozite 100°C da	8.2 mm ² /s	DIN 51562-1
Viskozite 40°C da	46.54 mm ² /s	DIN 51562-1
Viskozite indeksi VI	151	DIN ISO 2909
Past haroratli viskozite (CCS) - 35°C da	5710 mPa*s	ASTM D5293
Past haroratda nasoslanish viskozitesi (MRV) -35°C da	13.500 mPa*s	ASTM D4684
Qotish harorati	-45 °C	DIN ISO 3016
NOACK bug'lanishi	10 %	ASTM D5800
Yong'in chiqish harorati	230 °C	DIN EN ISO 2592
Ishqoriy son	10.1 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	0.94 %wt.	DIN 51575