

RAVENOL Hydraulikol TSX 46 (HVLP) gidravlik moyi

Yopishqoqlik: 46

Mineral



5 L

Mahsulot kodi:
1323205-005



10 L

Mahsulot kodi:
1323205-010



20 L

Mahsulot kodi:
1323205-020
Mahsulot kodi:
1323205-020-01-999
Shtrix-kod:
4014835760226



20 L, ecobox

Mahsulot kodi:
1323205-B20



60 L

Mahsulot kodi:
1323205-060



208 L

Mahsulot kodi:
1323205-208
Mahsulot kodi:
1323205-208-01-999
Shtrix-kod:
4014835760288



208 L, bosilgan barrel

Mahsulot kodi:
1323205-D28



1 000 L

Mahsulot kodi:
1323205-700

RAVENOL Hydraulikoel TSX 46 (HVLP) – HVLP toifasiga kiruvchi mineral gidravlik moy. Yuqori darajada tozalangan bazaviy moy va maxsus qo'shimchalar kompleksidan foydalanilishi natijasida barqaror yopishqoqlik indeksi, eskirish va korroziyaga qarshi ishonchli himoya, shuningdek muhrlovchi materiallarga nisbatan neytral munosabat ta'minlanadi.

RAVENOL Hydraulikoel TSX 46 (HVLP) gidravlik moylari og'ir ish sharoitida ishlovchi qurilish va kon texnikasi gidravlik tizimlarida qo'llaniladi, jumladan yuqori tezlikdagi va yuqori bosimli lapatkali, tishli va axial-porshenli nasoslar. Kumush yoki kumush bilan qoplangan detallar mavjud bo'lgan gidravlik tizimlarda qo'llash mumkin emas.

Qo'llash **Hydraulikol TSX 46** quyidagilarni ta'minlaydi:

- Doimiy yuqori yopishqoqlik indeksi
- Eskirishdan mukammal himoya
- Korroziyaga qarshi a'lo darajadagi himoya
- Ko'piklanishga qarshi himoya
- Plastmassali muhrlarga nisbatan neytral munosabat
- Past qotish harorati

Xususiyatlari

<i>Ism</i>	<i>Ma'nosi</i>	<i>Audit</i>
Talablarga mos keladi	AFNOR 48-603 HV, Cetop RP 91H HV, Cincinnati Milacron P-68, Cincinnati Milacron P-69, Cincinnati Milacron P-70, FZG 12, GM LH-04-1, GM LH-06-1, GM LH-15-1, Parker Denison HF-0, Parker Denison HF-1, Parker Denison HF-2, Sperry Vickers I-286-S, Sperry Vickers M-2950-S, U.S. Steel 127, U.S. Steel 136, Vickers Vane Pump	
Spetsifikatsiyalarga mos keladi	DIN 51524-3, ISO 6743-4 HV	
Zichlik 20°C da	855 g/cm ³	EN ISO 12185
Rang	Sariq	ingl
Viskozite 100°C da	7.9 mm ² /s	DIN 51562-1
Viskozite 40°C da	45 mm ² /s	DIN 51562-1
Viskozite indeksi VI	148	DIN ISO 2909
Qotish harorati	-42 °C	DIN ISO 3016
Yong'in chiqish harorati	232 °C	DIN EN ISO 2592
Tavsiyalar	AFNOR 48-603 HV, CETOP RP 91H HV, Cincinnati Milacron P-68 (HM-32), Cincinnati Milacron P-69 (HM-68), Cincinnati Milacron P-70 (HM-46), FZG 12, GM LH-04-1, GM LH-06-1, GM LH-15-1, Parker Denison HF-0, Parker Denison HF-1, Parker Denison HF-2, Sperry Vickers I-286-S, Sperry Vickers M-2950-S, US Steel 127, US Steel 136, Vickers Vane Pump	

OEM analoglari

Alpine

0100831, 0100832, 0100833

Scania

2252141

Volvo

11706210, VOE11706210, 15030580, VOE15030580, 11706211, VOE11706211, 11713238, VOE11713238, 15030482, VOE15030482

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
5 L	1323205-005-01-999	
60 L	1323205-060-01-999	
208 L	1323205-208-01-000	4014835642683 2200000043870